

COVE Comparison Chart

COVE PRODUCTS	LUMENS PER FT	WATTAGE PER FT	CCT'S	SIZE	LENGTHS	STANDARDS & CERTIFICATIONS
NANO	307-351	3.85 - 10.5	2700K - 4000K	L: 12in (304mm) W: 1 3/4in (45mm) H: 1in (25mm)	1FT & 4FT	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, RoHS, & WEEE Compliant. JA8-2019.
MINI COVE	448-1004	4.7 - 10	1800K - 6500K	L: 12in (304mm) W: 1 13/16in (46mm) H: 1 3/16in (30mm)	6IN, 1FT, & 4FT	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, RoHS, & WEEE Compliant. JA8-2019.
COVE	250-1257	4 - 10	2200K - 4000K	L: 12 3/8in (318mm) W: 2 7/16in (61mm) H: 2 3/8in (60mm)	1FT & 4FT	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
COVE EXTERIOR	250-1257	4 - 10	2200K - 4000K	L: 12 1/2in (318mm) W: 2 13/16in (71mm) H: 2 9/16in (65mm)	1FT & 4FT	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.